

# **EnMAP – An Advanced Optical Payload for Earth Observation**

**Hermann Kaufmann, Luis Guanter, Karl Segl, Sabine Chabrillat**

*German Research Center for Geosciences (GFZ)*

*Telegrafenberg A17, 14473 Potsdam, Germany*

*Phone: ++(49-331) 288-1190*

*e-mail: charly@gfz-potsdam.de*

**Stefan Hofer, Klaus-Peter Foerster, Bernhard Sang, Timo Stuffer**

*Kayser-Threde GmbH, Munich, Germany*

**Andreas Mueller, Rupert Mueller, Rudolf Richter**

*German Aerospace Establishment (DLR), Germany*

**Christian Chlebek, Godela Rossner**

*German Space Agency (DLR), Germany*

## **Abstract**

The potential of imaging spectroscopy to provide more and better information about the Earth system than traditional multispectral instruments is currently not counterbalanced by an equivalent availability of space-borne spectroscopy data. The Environmental Mapping and Analysis Program (EnMAP), a German hyperspectral mission scheduled for launch in 2013, is intended to cover this gap. The primary goal of EnMAP is to offer accurate, diagnostic information on the state and evolution of terrestrial ecosystems on a timely and frequent basis, and to allow for a detailed analysis of surface parameters with regard to the characterisation of vegetation canopies, rock/soil targets and coastal waters on a global scale. EnMAP is designed to record bio-physical, bio-chemical and geo-chemical variables to increase our understanding of biospheric/geospheric processes and to ensure the sustainability of our resources.

EnMAP will sample areas of 30 x 30 km<sup>2</sup> with a ground sampling distance (GSD) of 30 m, measuring in the 420-2450 nm range by means of two separate spectrometers covering the visible to near-infrared (VNIR) and short-wave infrared (SWIR) spectral regions. The mean spectral sampling distance and resolution is of 6.5 nm at the VNIR, and of 10 nm at the SWIR. Accurate radiometric and spectral responses are guaranteed by a required signal-to-noise ratio (SNR) of about 500:1 in the VNIR and about 150:1 in the SWIR, a radiometric calibration accuracy better than 5% and a spectral calibration uncertainty of 0.5 in the VNIR and 1 nm in the SWIR. An off-nadir pointing capability of up to 30° enables a target revisit time of 4 days.

Recent scientific activities have been focused on the development of a forward scene simulator to support hardware developments and the consolidation of the mission concept.

## **Introduction**

Hyperspectral remote sensing, often referred to as imaging spectroscopy, is based on the evaluation of radiance data measured in spectrally contiguous channels. The radiation reflected by the coupled surface-atmosphere system is registered in the visible to near-infrared (VNIR) and short-wave infrared (SWIR) spectral ranges. The detailed spectral characterization of atmospheric and surface absorption features provided by imaging spectrometers enables the use of robust inversion algorithms for the retrieval of geophysical information from the imaged area. The continuous spectral coverage provided by imaging spectrometers offers the possibility to design multi-purpose Earth observation missions, as the same system can be used for different thematic applications (e.g. agriculture, water or mineral mapping). However, the recognized potential of imaging spectroscopy to provide detailed diagnostic information about the Earth system than traditional multispectral instruments is currently not counterbalanced by an equivalent availability of hyperspectral satellite data.

The Environmental Mapping and Analysis Program (EnMAP), a German hyperspectral mission, is intended to cover this gap. EnMAP is a joint response of German Earth Observation (EO) research institutions, value-adding resellers and space industry to the increasing demand on accurate, quantitative information about the evolution of terrestrial ecosystems.

## **Objectives**

EnMAP hyperspectral capabilities will cover the visible, near-infrared and short-wave infrared wavelengths, EnMAP will provide high quality, standardized, and consistent data on a timely and frequent basis. The instrument performance allows for a detailed monitoring, characterization and parameter extraction of vegetation targets, rock and soils, and inland and coastal waters on a global scale.

- To provide high-spectral resolution observations of biophysical, biochemical and geochemical variables that will enable the improved retrieval of quantitative parameters needed by the users and not provided by operating multispectral sensors.
- To observe and develop a wide range of ecosystem parameters encompassing agriculture, forestry, soil/geological environments, and coastal zones and inland waters.
- To provide high-quality calibrated data and data products to be used as inputs for improved modelling and understanding of biospheric and geospheric processes.

## **Sensor Description**

EnMAP is designed to measure in the 420-2450 range by means of two separate spectrometers covering the VNIR and SWIR spectral regions. It will sample areas of 30x30 km<sup>2</sup> with a ground sampling distance (GSD) of 30 m. The mean spectral sampling distance and resolution is 6.5 nm in the VNIR, and 10 nm in the SWIR. Accurate radiometric and spectral responses are guaranteed by a required signal-to-noise ratio (SNR) about 500:1 in the VNIR and about 150:1 in the SWIR (for a reference radiance level given by 30% surface albedo, 30° sun zenith angle, 0.5 km above sea level and 21 km atmospheric visibility), radiometric calibration accuracy <5% and spectral calibration uncertainty of 0.5 nm in the

VNIR and 1 nm in the SWIR. An off-nadir pointing capability of up to 30° enables a revisit time of 4 days. A summary of essential mission parameters is displayed in Table 1.

Table 1. Summary of EnMAP sensor and orbit parameters

<b>Imaging principle</b>	Pushbroom-prism
<b>Spectral range</b>	VNIR: 420-1000 nm SWIR: 900-2450 nm
<b>Mean SSI</b>	VNIR: 6.5 nm SWIR: 10 nm
<b>SNR at reference radiance</b>	>500:1@ 495 nm (VNIR) >150:1@2200 nm (SWIR)
<b>Spectral calibration accuracy</b>	VNIR: 0.5 nm SWIR: 1 nm
<b>Spectral stability</b>	0.5 nm
<b>Radiometric calibration accuracy</b>	<5%
<b>Radiometric stability</b>	<2.5%
<b>Radiometric resolution</b>	14 bit
<b>Sensitivity to polarization</b>	<5%
<b>Spectral smile/keystone effect</b>	<20% of detector element
<b>GSD</b>	30 m
<b>Swath width</b>	30 km
<b>Geometric co-registration</b>	0.2×GSD
<b>Swath length (at least)</b>	1000 km/orbit
<b>Coverage</b>	Global in near-nadir mode ( $VZA \leq 5^\circ$ )
<b>Target revisit time</b>	23 days ( $VZA \leq 5^\circ$ ) 4 days ( $VZA \leq 30^\circ$ )
<b>Pointing accuracy</b>	100 m at sea level

### Ground Control and Satellite Operation Concept

The EnMAP space segment will rely on common RF equipment (standard S- and X-Band links), and will be completely compliant with the existing ground segment infrastructure. Mission control will be located at DLR-GSOC (German Space Observation Center) Oberpfaffenhofen with satellite commanding via Weilheim. Operational data reception facilities for small satellite missions dedicated to EO exist at the Neustrelitz X-Band ground station. Other international stations have already expressed their interest to receive EnMAP data and offer downlink capability, what would increase the throughput of data and attract additional user communities.

The EnMAP operations procedures can mostly be taken from previously flown German missions. In addition, it is assumed that for the launch and early orbit phase GSOC will cooperate with international S-Band stations operators.

### Data Processing and Archiving

The processing and archiving of the received EnMAP data will be under the responsibility of DLR-DFD (German Remote Sensing Data Center) in Oberpfaffenhofen. The processing chain comprises the conversion of the raw data to Level 0+ and Level 1. Level 1 and/or Level 2a/b data will be made available to participating scientists and value-adding companies via a mission dedicated user access portal. In order to reduce the amount of the data, only the Level 0+ data will be archived at DFD.

At DLR-DFD software packages already exist that fulfil the requirements of an operational and semi-automatic preprocessing of hyperspectral data from airborne sensors. These software tools are adapted to the needs of EnMAP and integrated in DLR's Data Information and Management System (DIMS), an automated processing environment with robot archive interface as established for the handling of satellite data.

Besides the handling of automated data pre-processing and archiving, DIMS provides user information services such as on-line and off-line delivery, post-processing, a product library, ordering control and production control. Due to the modular design of DIMS both the automated pre-processing (system correction, radiometric calibration, combined geocoding and atmospheric correction) and the integration of newly developed information products during the operation period of EnMAP can be assured. Quality checks will be carried out in every step of the processing chain (e.g. histograms of bands, signal-to-noise ratio computation for each channel, channel cross correlation analysis, etc.).

Out of a number of suitable launchers, compatible with the EnMAP requirements and characteristics, the Indian PSLV has been selected. The necessary I/Fs with the DLR-GSOC are already established.

### **Preparatory Activities**

Main efforts during the transfer situation from phase B to C has been the consolidation of the instrument design and the preparation of the ground processing chain. A prototype including all the processing modules for the conversion from Level 0+, digital numbers, to geometrically-corrected surface reflectance is already available. The different modules have been designed in parallel with the instrument development so that the processing scheme is consistent with the particular instrument functioning and could compensate for hardware limitations and enhance the data quality by software means.

Further activities have been focused on the support of industrial developments and the consolidation of the mission concept. With this framework, a scene simulator generating EnMAP-like data under realistic conditions has been implemented. It enables the definition of optimal instrument configurations for radiometric, spectral and geometric parameters. The simulator covers the 400-2500 nm spectral region and generates digital number images of 1000x1000 pixels with a GSD of 30 m. Variables are i.e. spatially coherent and non-coherent noise, drop-outs and calibration coefficients according to the instrument dynamic range. The simulator is also used to prepare algorithms for correction of defects and to calculate parameter retrieval quality.

An EnMAP-specific software environment for the interactive processing of data is being jointly designed by the Geomatics lab of the Humboldt University of Berlin and the GFZ. Tools for the pre-processing of EnMAP data and the derivation of higher-level biophysical products are to be included in this software. The main objectives are to facilitate the derivation of higher-level products by consolidated processing algorithms optimized for EnMAP data, and to provide tools for user-driven data pre-processing. Presently, a plan for the EnMAP post-launch calibration and product validation is already under development. The routinary EnMAP calibration strategy based on the monitoring and processing of the on-board measured instrument parameters is being developed at DLR-DFD and DLR-IMF. Complementing this calibration plan, a strategy for the support of in-flight calibration devices with

vicarious calibration and validation activities, as well as the interaction between EnMAP and other co-existing EO missions for calibration and scientific purposes is being developed at GFZ. Such a plan is intended to complement the GS measurements with some others that are not considered in the monitoring and calibration plan, as well as to provide backup information on those parameters that are already evaluated by other means. In addition, representative error figures of EnMAP products will be estimated using ground-based measurements. For example, image-based data quality check, spectral calibration analysis, geometric calibration accuracy and ground-based validation activities will be addressed in this strategy.

## Summary

In this paper, an overview has been given of the current status of the EnMAP hyperspectral mission. This project is a joint venture, where the DLR-Agency acts as project manager, the GFZ in Potsdam has the scientific lead, Kayser-Threde GmbH is the industrial prime for the sensor, OHB-Systems AG provides the bus and the DLR-DFD is responsible for the ground segment. Currently, EnMAP is in the middle of phase C. The launch is scheduled for 2013 aboard an Indian PSLV. The main objective of EnMAP is the repeated global derivation of biophysical, biochemical and geochemical variables from a range of surface covers. Main current EnMAP activities are the consolidation of the instrument design and preparatory works resp. algorithm development for calibration, validation, and (pre)processing. In parallel, a preparatory science program for researchers of different disciplines and workshops and summer schools for young scientist have been set up.

## Literature

- Kaufmann, H., Segl, K., Guanter, L., Hofer, S., T. Stuffer, T., Bach, H., Mueller, A., Richter, R., and Chlebek, C., (2008) Environmental mapping and analysis program (EnMAP) – Recent advances and status. Proc. *IGARSS '08*, Boston, US, CD-ROM.
- Guanter, L. Richter, R. and Kaufmann, H., (2009) On the application of the MODTRAN4 atmospheric radiative transfer code to optical remote sensing. *International Journal of Remote Sensing*, 30:6, 1407-1424.
- Guanter, L., Segl, K., and Kaufmann, H., (2009) Simulation of optical remote sensing scenes with application to the EnMAP hyperspectral mission. *IEEE-Transactions on Geoscience and Remote Sensing*, 47/7, 2340-2351.
- Guanter, L., Segl, K., Sang, B., Alonso, L., Kaufmann, H., and Moreno, J., (2009) Scene-based spectral calibration assessment of high spectral resolution imaging spectrometers. *Optics Express*, 17-14, 11594-11606, 10.1364/OE.17.011594.
- Stuffer, T., Förster, K., Hofer, S., Leipold, M., Sang, B., Kaufmann, H., Penné, B., Mueller, A., and Chlebek, C., (2009) Hyperspectral imaging - An advanced instrument concept for the EnMAP mission (Environmental Mapping and Analysis Program), *Acta Astronautica*, 65, 1107–1112.

## Acknowledgement

The work presented in this paper was performed on behalf of the German Space Agency with funds of the German Federal Ministry of Economic Affairs and Technology.